


# MANUAL GEAR R20

Gearbox with reduction 1:20 self-breaking can be fixed to the side wall together with a telescopic arm or mounted on a sliding guide for vertical tube  $\varnothing 27/32/33$ . It has been devised for plastic side wall roll-up systems of medium/large lengths. It has stainless steel worm gear, bronze wheel, and shaft  $\varnothing 27$  and crank handle in stainless steel, too. Maximum advised length is 70/75 m.




**R20**

|                         |        |
|-------------------------|--------|
| REDUCTION               | 1-20   |
| INPUT TORQUE            | 15 Nm  |
| OUTPUT TORQUE           | 80 Nm  |
| MAX LENGTH WITH PIPE 27 | 90     |
| MAX LENGTH WITH PIPE 60 | 65/70  |
| WEIGHT GEAR             | 5,5 kg |

# MANUAL GEAR R40

Gearbox with reduction 1:40 self-breaking can be fixed to the side wall together with a telescopic arm or mounted on a sliding guide for vertical tube  $\varnothing 27/32/33$ . It has been devised for plastic side wall roll-up systems of great lengths. It has stainless steel worm gear, bronze wheel, shaft  $\varnothing 27$  and crank handle in stainless steel, too. Maximum advised length is 90/115 m.



**R40**

|                         |        |
|-------------------------|--------|
| REDUCTION               | 1-40   |
| INPUT TORQUE            | 20 Nm  |
| OUTPUT TORQUE           | 110 Nm |
| MAX LENGTH WITH PIPE 27 | 110    |
| MAX LENGTH WITH PIPE 60 | 75/80  |
| WEIGHT GEAR             | 5,5 kg |